

Environmental Data Sheet

ECOSYS P4060dn

Environmental Management	This device is manufactured in production facilities that work with an environmental management system in accordance with ISO 14001.	
Power Consumption Heat Emission	Maximum (at switch on, full options): 1750 W 6300 kJ/h Printing: 820 W 2952 kJ/h Ready: 40 W 144 kJ/h Low power mode: 40 W 144 kJ/h Sleep-mode: 1 W 3.6 kJ/h Off-mode: 0.3 W 1.1 kJ/h Plug-in Off-mode: 0.1 W 0.4 kJ/h	
Typical Power Consumption (TEC) (according to ENERGY STAR 3.0)	0.90 kWh/week (8960 pages/week)	
Installation Notes	The unit should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the printer in dusty rooms, and protect against ammonia vapors. Please follow the instructions in the user manual.	
Humidity	10% – 80%	
Room Temperature	10°C – 32.5°C	
Noise Emission (according to ISO 7779)	Operation	Ready
	Surface sound pressure level (measurement in 1m distance, average of single measurements)	
	[dB(A) L _{pA}]	55.8 32.4
	Operator position	
	[dB(A) L _{pA}]	59.0 36.7
	Sound power level (DE-UZ 219)	
	[dB(A) L _{WA} d]	72.9
Light Source	Exposure drum: Laser	
Emission	According to DE-UZ 219	
	TVOC (Operation):	5.83 mg/h
	TVOC (Ready):	0.061 mg/h
	Benzene:	< limit of quantitation
	Styrene:	0.18 mg/h
	Ozone:	< limit of detection
	Dust:	0.14 mg/h
ECOLabel	Exposure drum: Laser Product related environmental labels in Germany/Austria: Blue Angel DE-UZ 219 Status: In preparation List of certified KYOCERA products can be found here: https://www.blauer-engel.de/en/products/brands/kyocera Others countries: Please refer to the local country information.	

effective 11/2021 – Errors and omissions excepted